

LA

PROCESSES AND PROPERTIES. See.

Coking of pitch tar. N. A. Nikoskit, M. A. Stepanenko and N. A. Kabachenko. *Coke and Chem.* (U. S. S. R.), 6, No. 4, 43-7 (1936); *Chimie & Industrie* 37, 51-2. The tar formed during the coking of pitch can itself be coked; thus the total yield of electrode C can be increased from 65% to 78-80%, on the original pitch. The most rational procedure is to coke the pitch tar separately and remove the secondary tar from the cycle, the yield of "secondary" tar being 10% of the pitch. Continued circulation of the pitch tar during the coking of the pitch-tar mixt. influences the chem. properties of the coke obtained. A. Papineau-Couture

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

1911-1912

1913-1914

1915-1916

1917-1918

1919-1920

1921-1922

1923-1924

1925-1926

1927-1928

1929-1930

1931-1932

1933-1934

1935-1936

1937-1938

1939-1940

1941-1942

1943-1944

1945-1946

1947-1948

1949-1950

1951-1952

1953-1954

1955-1956

1957-1958

1959-1960

1961-1962

1963-1964

1965-1966

1967-1968

1969-1970

1971-1972

1973-1974

1975-1976

1977-1978

1979-1980

1981-1982

1983-1984

1985-1986

1987-1988

1989-1990

1991-1992

1993-1994

1995-1996

1997-1998

1999-2000

2001-2002

2003-2004

2005-2006

2007-2008

2009-2010

2011-2012

2013-2014

2015-2016

2017-2018

2019-2020

2021-2022

2023-2024

2025-2026

2027-2028

2029-2030

2031-2032

2033-2034

2035-2036

2037-2038

2039-2040

2041-2042

2043-2044

2045-2046

2047-2048

2049-2050

2051-2052

2053-2054

2055-2056

2057-2058

2059-2060

2061-2062

2063-2064

2065-2066

2067-2068

2069-2070

2071-2072

2073-2074

2075-2076

2077-2078

2079-2080

2081-2082

2083-2084

2085-2086

2087-2088

2089-2090

2091-2092

2093-2094

2095-2096

2097-2098

2099-2100

2101-2102

2103-2104

2105-2106

2107-2108

2109-2110

2111-2112

2113-2114

2115-2116

2117-2118

2119-2120

2121-2122

2123-2124

2125-2126

2127-2128

2129-2130

2131-2132

2133-2134

2135-2136

2137-2138

2139-2140

2141-2142

2143-2144

2145-2146

2147-2148

2149-2150

2151-2152

2153-2154

2155-2156

2157-2158

2159-2160

2161-2162

2163-2164

2165-2166

2167-2168

2169-2170

2171-2172

2173-2174

2175-2176

2177-2178

2179-2180

2181-2182

2183-2184

2185-2186

2187-2188

2189-2190

2191-2192

2193-2194

2195-2196

2197-2198

2199-2200

2201-2202

2203-2204

2205-2206

2207-2208

2209-2210

2211-2212

2213-2214

2215-2216

2217-2218

2219-2220

2221-2222

2223-2224

2225-2226

2227-2228

2229-2230

2231-2232

2233-2234

2235-2236

2237-2238

2239-2240

2241-2242

2243-2244

2245-2246

2247-2248

2249-2250

2251-2252

2253-2254

2255-2256

2257-2258

2259-2260

2261-2262

2263-2264

2265-2266

2267-2268

2269-2270

2271-2272

2273-2274

2275-2276

2277-2278

2279-2280

2281-2282

2283-2284

2285-2286

2287-2288

2289-2290

2291-2292

2293-2294

2295-2296

2297-2298

2299-2300

2301-2302

2303-2304

2305-2306

2307-2308

2309-2310

2311-2312

2313-2314

2315-2316

2317-2318

2319-2320

2321-2322

2323-2324

2325-2326

2327-2328

2329-2330

2331-2332

2333-2334

2335-2336

2337-2338

2339-2340

2341-2342

2343-2344

2345-2346

2347-2348

2349-2350

2351-2352

2353-2354

2355-2356

2357-2358

2359-2360

2361-2362

2363-2364

2365-2366

2367-2368

2369-2370

2371-2372

2373-2374

2375-2376

2377-2378

2379-2380

2381-2382

2383-2384

2385-2386

2387-2388

2389-2390

2391-2392

2393-2394

2395-2396

2397-2398

2399-2400

2401-2402

2403-2404

2405-2406

2407-2408

2409-2410

2411-2412

2413-2414

2415-2416

2417-2418

2419-2420

2421-2422

2423-2424

2425-2426

2427-2428

2429-2430

2431-2432

2433-2434

2435-2436

2437-2438

2439-2440

2441-2442

2443-2444

2445-2446

2447-2448

2449-2450

2451-2452

2453-2454

2455-2456

2457-2458

2459-2460

<

13

Production of high melting coumarone resin at the Ruzhichensky factory. M. A. Stepanenko and L. D. Ginzman. *Kokhi Chim* 1938, No. 7, 435. The coal tar xylene fraction, b. 160-180°, is heated with vigorous stirring at 60° with 1.5 vols. of 92-5% H₂SO₄. The product is thoroughly washed with H₂O, aq. NaOH, and H₂O, and unpolymerized constituents are removed by steam-distn. The residual resin, subjected to fractional distn. *in vacuo*, yields a product m. 85-98°. B. C. P. A.

ASH 51.4 METALLURGICAL LITERATURE CLASSIFICATION

Direction of tar vapors and gases inside of the charge during coking. I. N. A. Nikol'skii and M. A. Stepanenko. *Khim. Tverdogo Topliva* 9, 28-42 (1938).—The direction of tar vapors and gases inside of the charge was studied in a special app. consisting of a furnace with one-sided heating, a coking chamber covered with lid which has partitions dividing the free space above the charge into independent portions, a condensing app. for removal of tar, thermocouples with galvanometer and manometers for measuring temp. and pressure. The duration of expts. was 3.5-4 hrs., which permitted the temp. of the charge at the unheated side to reach 500-600°, whereas the temp. of the heated side was kept at 950°. Tar vapors inside of the coking charge have no basic direction along the cracks and along the walls; a plastic seam did not create a great resistance for the movement of gases and vapors; gases and vapors evolving from the coking charge have a main direction along the verticals, i. e., proceed along those zones from which they evolve. Seventeen references.

A. A. Podgorny

PROCESS AND PROPERTIES INDEX																																																																																																																																																											
COMMON ELEMENTS													COMMON VARIABLE INDEX																																																																																																																																														
<p> C7 21 </p> <p> treatment of coal at medium temperatures. N. A. Nikol'skii and M. A. Stepanenko. <i>Coke and Chem.</i> (U. S. S. R.) 1938, No. 12, 11-12; <i>Khim. Referat. Zhur.</i> 2, No. 4, 113-14 (1939).—The mixt. (which is coked at 600-800°) contains 20-55% of volatile substances and 7% of ash. When a larger amt. of ash is present the coal is enriched by the wet method and dried. After its removal from the furnace the coke is mixed with water. The "fixed carbon" contains moisture 2%, volatile substances 4-12% and ash 9-10% and has a heat content of 7200-7300 cal. From the treatment of the coal a tar is obtained which contains 35-45% of phenols in oils from which C_6H_5OH and α-, m- and p-$C_6H_4C_6H_4OH$ can be obtained. Treatment of gas coals yields up to 8.5% of tar, of which 1.0-1.1% is motor fuel and 2% is Diesel engine fuel. W. R. Henn </p>																																																																																																																																																											
ASB-ILA METALLURGICAL LITERATURE CLASSIFICATION																																																																																																																																																											
<table border="1"> <thead> <tr> <th colspan="13">RECORD #1</th> <th colspan="13">RECORD #2</th> </tr> <tr> <th colspan="13">SEARCHED MAP ONLY GEL</th> <th colspan="13">RECORD ONLY GEL</th> </tr> </thead> <tbody> <tr> <td colspan="13"> <table border="1"> <tr><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </table> </td> <td colspan="13"> <table border="1"> <tr><td>14</td><td>15</td><td>16</td><td>17</td><td>18</td><td>19</td><td>20</td><td>21</td><td>22</td><td>23</td><td>24</td><td>25</td><td>26</td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </table> </td> </tr> </tbody> </table>																										RECORD #1													RECORD #2													SEARCHED MAP ONLY GEL													RECORD ONLY GEL													<table border="1"> <tr><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </table>													1	2	3	4	5	6	7	8	9	10	11	12	13														<table border="1"> <tr><td>14</td><td>15</td><td>16</td><td>17</td><td>18</td><td>19</td><td>20</td><td>21</td><td>22</td><td>23</td><td>24</td><td>25</td><td>26</td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </table>													14	15	16	17	18	19	20	21	22	23	24	25	26													
RECORD #1													RECORD #2																																																																																																																																														
SEARCHED MAP ONLY GEL													RECORD ONLY GEL																																																																																																																																														
<table border="1"> <tr><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </table>													1	2	3	4	5	6	7	8	9	10	11	12	13														<table border="1"> <tr><td>14</td><td>15</td><td>16</td><td>17</td><td>18</td><td>19</td><td>20</td><td>21</td><td>22</td><td>23</td><td>24</td><td>25</td><td>26</td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </table>													14	15	16	17	18	19	20	21	22	23	24	25	26																																																																																											
1	2	3	4	5	6	7	8	9	10	11	12	13																																																																																																																																															
14	15	16	17	18	19	20	21	22	23	24	25	26																																																																																																																																															

1ST AND 2ND CODES																										3RD AND 4TH CODES																									
PROCESSING AND PROPERTIES INDEX																										1ST AND 2ND CODES																									
<p>Production of coumarone resin with a softening temperature of 100-150°. M. A. Stepanenko and A. E. Minskaya. <i>Coke and Chem. (U. S. S. R.)</i> 1940, No. 2, 33 G. Data obtained in lab. expts. on the production of coumarone resin are given and the results of some tests on an industrial scale are also described. The process used involved the polymerization of the xylene fraction and of the xylene-heavy (Vershinn, C. A. 30, 3028) fraction with anhyd. $AlCl_3$. In the first case the softening temp. of the resin obtained was 100-130° and in the second up to 150°. A higher-grade resin was obtained with $AlCl_3$ than with H_2SO_4. The raw material had to be preheated to 45° before adding the $AlCl_3$. After polymerization and setting, the product was filtered and washed with H_2O and, if necessary, with 15% aq. $NaOH$ until neutral. Unpolymerized compds. and liquid polymerides are then distilled off to obtain the solid resin. The raw material fraction should contain not greater than 30% of polymerizable compds. and should be added, if necessary.</p> <p>B. C. P. A</p>																										13																									
ASB-5LA METALLURGICAL LITERATURE CLASSIFICATION																										1ST AND 2ND CODES																									
1ST AND 2ND CODES																										1ST AND 2ND CODES																									

17

PRELIMINARY AND TENTATIVE INDEX

Obtaining coumarone resins by thermal polymerization
M. A. Stepanenko and A. E. Minskaya. *Coke and Chem*
(U. S. S. R.) 11; No. 5, 29-32 (1941); *Chem. Zentr.* 1943
I, 1720-1; cf. C. A. 36, 23658. — The styrene, indene and
coumarone fractions from the heavy xylene fraction b
140-160° can be thermally polymerized without use of H₂
SO₄. When polymerization occurs under reflux, the prod-
uct has a higher mol. wt. than when reaction occurs at
220° and 6-7 atm. in an autoclave. The indene fraction
gives a lower yield of more unsatd. resin with a lower mol.
wt. than that from styrene. Longer polymerization raises
the d. and yield of the resins, but does not change the mol.
wt. This is altered only by temp.; lower temp. produces
resins with higher mol. wt. The resin formed by heating
at 220° and 6-7 atm. for 48-50 hrs. softens at 110°. The
yield is 50-80%, and the unpolymerized residue can be
polymerized later by addn. of H₂SO₄. H. M. L.

COMMON VARIABLES INDEX

ASAC 35A METALLURGICAL LITERATURE CLASSIFICATION

13001 13002 13003 13004 13005 13006 13007 13008 13009 13010 13011 13012 13013 13014 13015 13016 13017 13018 13019 13020 13021 13022 13023 13024 13025 13026 13027 13028 13029 13030 13031 13032 13033 13034 13035 13036 13037 13038 13039 13040 13041 13042 13043 13044 13045 13046 13047 13048 13049 13050 13051 13052 13053 13054 13055 13056 13057 13058 13059 13060 13061 13062 13063 13064 13065 13066 13067 13068 13069 13070 13071 13072 13073 13074 13075 13076 13077 13078 13079 13080 13081 13082 13083 13084 13085 13086 13087 13088 13089 13090 13091 13092 13093 13094 13095 13096 13097 13098 13099 13100 13101 13102 13103 13104 13105 13106 13107 13108 13109 13110 13111 13112 13113 13114 13115 13116 13117 13118 13119 13120 13121 13122 13123 13124 13125 13126 13127 13128 13129 13130 13131 13132 13133 13134 13135 13136 13137 13138 13139 13140 13141 13142 13143 13144 13145 13146 13147 13148 13149 13150 13151 13152 13153 13154 13155 13156 13157 13158 13159 13160 13161 13162 13163 13164 13165 13166 13167 13168 13169 13170 13171 13172 13173 13174 13175 13176 13177 13178 13179 13180 13181 13182 13183 13184 13185 13186 13187 13188 13189 13190 13191 13192 13193 13194 13195 13196 13197 13198 13199 13200 13201 13202 13203 13204 13205 13206 13207 13208 13209 13210 13211 13212 13213 13214 13215 13216 13217 13218 13219 13220 13221 13222 13223 13224 13225 13226 13227 13228 13229 13230 13231 13232 13233 13234 13235 13236 13237 13238 13239 13240 13241 13242 13243 13244 13245 13246 13247 13248 13249 13250 13251 13252 13253 13254 13255 13256 13257 13258 13259 13260 13261 13262 13263 13264 13265 13266 13267 13268 13269 13270 13271 13272 13273 13274 13275 13276 13277 13278 13279 13280 13281 13282 13283 13284 13285 13286 13287 13288 13289 13290 13291 13292 13293 13294 13295 13296 13297 13298 13299 13300 13301 13302 13303 13304 13305 13306 13307 13308 13309 13310 13311 13312 13313 13314 13315 13316 13317 13318 13319 13320 13321 13322 13323 13324 13325 13326 13327 13328 13329 13330 13331 13332 13333 13334 13335 13336 13337 13338 13339 13340 13341 13342 13343 13344 13345 13346 13347 13348 13349 13350 13351 13352 13353 13354 13355 13356 13357 13358 13359 13360 13361 13362 13363 13364 13365 13366 13367 13368 13369 13370 13371 13372 13373 13374 13375 13376 13377 13378 13379 13380 13381 13382 13383 13384 13385 13386 13387 13388 13389 13390 13391 13392 13393 13394 13395 13396 13397 13398 13399 13400 13401 13402 13403 13404 13405 13406 13407 13408 13409 13410 13411 13412 13413 13414 13415 13416 13417 13418 13419 13420 13421 13422 13423 13424 13425 13426 13427 13428 13429 13430 13431 13432 13433 13434 13435 13436 13437 13438 13439 13440 13441 13442 13443 13444 13445 13446 13447 13448 13449 13450 13451 13452 13453 13454 13455 13456 13457 13458 13459 13460 13461 13462 13463 13464 13465 13466 13467 13468 13469 13470 13471 13472 13473 13474 13475 13476 13477 13478 13479 13480 13481 13482 13483 13484 13485 13486 13487 13488 13489 13490 13491 13492 13493 13494 13495 13496 13497 13498 13499 13500 13501 13502 13503 13504 13505 13506 13507 13508 13509 13510 13511 13512 13513 13514 13515 13516 13517 13518 13519 13520 13521 13522 13523 13524 13525 13526 13527 13528 13529 13530 13531 13532 13533 13534 13535 13536 13537 13538 13539 13540 13541 13542 13543 13544 13545 13546 13547 13548 13549 13550 13551 13552 13553 13554 13555 13556 13557 13558 13559 13560 13561 13562 13563 13564 13565 13566 13567 13568 13569 13570 13571 13572 13573 13574 13575 13576 13577 13578 13579 13580 13581 13582 13583 13584 13585 13586 13587 13588 13589 13590 13591 13592 13593 13594 13595 13596 13597 13598 13599 13600 13601 13602 13603 13604 13605 13606 13607 13608 13609 13610 13611 13612 13613 13614 13615 13616 13617 13618 13619 13620 13621 13622 13623 13624 13625 13626 13627 13628 13629 13630 13631 13632 13633 13634 13635 13636 13637 13638 13639 13640 13641 13642 13643 13644 13645 13646 13647 13648 13649 13650 13651 13652 13653 13654 13655 13656 13657 13658 13659 13660 13661 13662 13663 13664 13665 13666 13667 13668 13669 13670 13671 13672 13673 13674 13675 13676 13677 13678 13679 13680 13681 13682 13683 13684 13685 13686 13687 13688 13689 13690 13691 13692 13693 13694 13695 13696 13697 13698 13699 13700 13701 13702 13703 13704 13705 13706 13707 13708 13709 13710 13711 13712 13713 13714 13715 13716 13717 13718 13719 13720 13721 13722 13723 13724 13725 13726 13727 13728 13729 13730 13731 13732 13733 13734 13735 13736 13737 13738 13739 13740 13741 13742 13743 13744 13745 13746 13747 13748 13749 13750 13751 13752 13753 13754 13755 13756 13757 13758 13759 13760 13761 13762 13763 13764 13765 13766 13767 13768 13769 13770 13771 13772 13773 13774 13775 13776 13777 13778 13779 13780 13781 13782 13783 13784 13785 13786 13787 13788 13789 13790 13791 13792 13793 13794 13795 13796 13797 13798 13799 13800 13801 13802 13803 13804 13805 13806 13807 13808 13809 13810 13811 13812 13813 13814 13815 13816 13817 13818 13819 13820 13821 13822 13823 13824 13825 13826 13827 13828 13829 13830 13831 13832 13833 13834 13835 13836 13837 13838 13839 13840 13841 13842 13843 13844 13845 13846 13847 13848 13849 13850 13851 13852 13853 13854 13855 13856 13857 13858 13859 13860 13861 13862 13863 13864 13865 13866 13867 13868 13869 13870 13871 13872 13873 13874 13875 13876 13877 13878 13879 13880 13881 13882 13883 13884 13885 13886 13887 13888 13889 13890 13891 13892 13893 13894 13895 13896 13897 13898 13899 13900 13901 13902 13903 13904 13905 13906 13907 13908 13909 13910 13911 13912 13913 13914 13915 13916 13917 13918 13919 13920 13921 13922 13923 13924 13925 13926 13927 13928 13929 13930 13931 13932 13933 13934 13935 13936 13937 13938 13939 13940 13941 13942 13943 13944 13945 13946 13947 13948 13949 13950 13951 13952 13953 13954 13955 13956 13957 13958 13959 13960 13961 13962 13963 13964 13965 13966 13967 13968 13969 13970 13971 13972 13973 13974 13975 13976 13977 13978 13979 13980 13981 13982 13983 13984 13985 13986 13987 13988 13989 13990 13991 13992 13993 13994 13995 13996 13997 13998 13999 14000 14001 14002 14003 14004 14005 14006 14007 14008 14009 14010 14011 14012 14013 14014 14015 14016 14017 14018 14019 14020 14021 14022 14023 14024 14025 14026 14027 14028 14029 14030 14031 14032 14033 14034 14035 14036 14037 14038 14039 14040 14041 14042 14043 14044 14045 14046 14047 14048 14049 14050 14051 14052 14053 14054 14055 14056 14057 14058 14059 14060 14061 14062 14063 14064 14065 14066 14067 14068 14069 14070 14071 14072 14073 14074 14075 14076 14077 14078 14079 14080 14081 14082 14083 14084 14085 14086 14087 14088 14089 14090 14091 14092 14093 14094 14095 14096 14097 14098 14099 14100 14101 14102 14103 14104 14105 14106 14107 14108 14109 14110 14111 14112 14113 14114 14115 14116 14117 14118 14119 14120 14121 14122 14123 14124 14125 14126 14127 14128 14129 14130 14131 14132 14133 14134 14135 14136 14137 14138 14139 14140 14141 14142 14143 14144 14145 14146 14147 14148 14149 14150 14151 14152 14153 14154 14155 14156 14157 14158 14159 14160 14161 14162 14163 14164 14165 14166 14167 14168 14169 14170 14171 14172 14173 14174 14175 14176 14177 14178 14179 14180 14181 14182 14183 14184 14185 14186 14187 14188 14189 14190 14191 14192 14193 14194 14195 14196 14197 14198 14199 14200 14201 14202 14203 14204 14205 14206 14207 14208 14209 14210 14211 14212 14213 14214 14215 14216 14217 14218 14219 14220 14221 14222 14223 14224 14225 14226 14227 14228 14229 14230 14231 14232 14233 14234 14235 14236 14237 14238 14239 14240 14241 14242 14243 14244 14245 14246 14247 14248 14249 14250 14251 14252 14253 14254 14255 14256 14257 14258 14259 14260 14261 14262 14263 14264 14265 14266 14267 14268 14269 14270 14271 14272 14273 14274 14275 14276 14277 14278 14279 14280 14281 14282 14283 14284 14285 14286 14287 14288 14289 14290 14291 14292 14293 14294 14295 14296 14297 14298 14299 14300 14301 14302 14303 14304 14305 14306 14307 14308 14309 14310 14311 14312 14313 14314 14315 14316 14317 14318 14319 14320 14321 14322 14323 14324 14325 14326 14327 14328 14329 14330 14331 14332 14333 14334 14335 14336 14337 14338 14339 14340 14341 14342 14343 14344 14345 14346 14347 14348 14349 14350 14351 14352 14353 14354 14355 14356 14357 14358 14359 14360 14361 14362 14363 14364 14365 14366 14367 14368 14369 14370 14371 14372 14373 14374 14375 14376 14377 14378 14379 14380 14381 14382 14383 14384 14385 14386 14387 14388 14389 14390 14391 14392 14393 14394 14395 14396 14397 14398 14399 14400 14401 14402 14403 14404 14405 14406 14407 14408 14409 14410 14411 14412 14413 14414 14415 14416 14417 14418 14419 14420 14421 14422 14423 14424 14425 14426 14427 14428 14429 14430 14431 14432 14433 14434 14435 14436 14437 14438 14439 14440 14441 14442 14443 14444 14445 14446 14447 14448 14449 14450 14451 14452 14453 14454 14455 14456 14457 14458 14459 14460 14461 14462 14463 14464 14465 14466 14467 14468 14469 14470 14471 14472 14473 14474 14475 14476 14477 14478 14479 14480 14481 14482 14483 14484 14485 14486 14487 14488 14489 14490 14491 14492 14493 14494 14495 14496 14497 14498 14499 14500 14501 14502 14503 14504 14505 14506 14507 14508 14509 14510 14511 14512 14513 14514 14515 14516 14517 14518 14519 14520 14521 14522 14523 14524 14525 14526 14527 14528 14529 14530 14531 14532 14533 14534 14535 14536 14537 14538 14539 14540 14541 14542 14543 14544 14545 14546 14547 14548 14549 14550 14551 14552 14553 14554 14555 14556 14557 14558 14559 14560 14561 14562 14563 14564 14565 14566 14567 14568 14569 14570 14571 14572 14573 14574 14575 14576 14577 14578 14579 14580 14581 14582 14583 14584 14585 14586 14587 14588 14589 14590 14591 14592 14593 14594 14595 14596 14597 14598 14599 14600 14601 14602 14603 14604 14605 14606 14607 14608 14609 14610 14611 14612 14613 14614 14615 14616 14617 14618 14619 14620 14621 14622 14623 14624 14625 14626 14627 14628 14629 14630 14631 14632 14633 14634 14635 14636 14637 14638 14639 14640 14641 14642 14643 14644 14645 14646 14647 14648 14649 14650 14651 14652 14653 14654 14655 14656 14657 14658 14659 14660 14661 14662 14663 14664 14665 14666 14667 14668 14669 14670 14671 14672 14673 14674 14675 14676 14677 14678 14679 14680 14681 14682 14683 14684 14685 14686 14687 14688 14689 14690 14691 14692 14693 14694 14695 14696 14697 14698 14699 14700 14701 14702 14703 14704 14705 14706 14707 14708 14709 14710 14711 14712 14713 14714 14715 14716 14717 14718 14719 14720 14721 14722 14723 14724 14725 14726 14727 14728 14729 14730 14731 14732 14733 14734 14735 14736 14737 14738 14739 14740 14741 14742 14743 14744 14745 14746 14747 14748 14749 14750 14751 14752 14753 14754 14755 14756 14757 14758 14759 14760 14761 14762 14763 14764 14765 14766 14767 14768 14769 14770 14771 14772 14773 14774 14775 14776 14777 14778 14779 14780 14781 14782 14783 14784 14785 14786 14787 14788 14789 14790 14791 14792 14793 14794 14795 14796 14797 14798 14799 14800 14801 14802 14803 14804 14805 14806 14807 14808 14809 14810 14811 14812 14813 14814 14815 14816 14817 14818 14819 14820 14821 14822 14823 14824 14825 14826 14827 14828 14829 14830 14831 14832 14833 14834 14835 14836 14837 14838 14839 14840 14841 14842 14843 14844 14845 14846 14847 14848 14849 14850 14851 14852 14853 14854 14855 14856 14857 14858 14859 14860 14861 14862 14863 14864 14865 14866 14867 14868 14869 14870 14871 14872 14873 14874 14875 14876 14877 14878 14879 14880 14881 14882 14883 14884 14885 14886 14887 14888 14889 14890 14891 14892 14893 14894 14895 14896 14897 14898 14899 14900 14901 14902 14903 14904 14905 14906 14907 14908 14909 14910 14911 14912 14913 14914 14915 14916 14917 14918 14919 14920 14921 14922 14923 14924 14925 14926 14927 14928 14929 14930 14931 14932 14933 14934 14935 14936 14937 14938 14939 14940 14941 14942 14943 14944 14945 14946 14947 14948 14949 14950 14951 14952 14953 14954 14955 14956 14957 14958 14959 14960 14961 14962 14963 1

68-1-9/21

AUTHOR: Stepanenko, M.A., Doctor of Technical Sciences, and
Matusyak, N.I., Gogoleva, T.Ya., Engineers.

TITLE: Coal Oil Pitch as a Binding Material for Briquetting Coals.
 (Uglemaslyanny pek - svyazuyushchiy material dlya briket-irovaniya ugley)

PERIODICAL: Koks i Khimiya, 1957, No.1, pp. 32 - 35 (USSR)

ABSTRACT: A product obtained by a thermal treatment of a mixture of coal and high boiling fractions of pitch distillates of anthracene fraction II, as a solvent is called coal oil pitch. In the paper the preparation of coal oil pitch and its further use as a binder for briquetting coal is described. Coal oil pitches were prepared from coals T, TK, K and TC and a mixture of anthracene fraction II and heavy pitch distillates (ratio 1:1.2). Properties of coals and solvents are given in Tables 1 and 2, respectively. Preparation of coal oil pitch: coal crushed to 3 mm is mixed with the solvent (% of solvent for T, TK and K - 32% and for TC - 24%) and heated for 3 hours at 360 - 380 °C. The yield and properties of coal oil pitch obtained are given in Table 3. Coal T was briquetted under the following conditions: softening temperature of coal oil pitch - 65 - 75 °C; proportion of the binder 12%; fineness of coal - crushed to 3 mm; temperature of mixing and pressing 95 °C.

APPROVED FOR RELEASE: 08/25/2000 CIA-RDP86-00513R001653120020-1"

68-1-9/21

Coal Oil Pitch as a Binding Material for Briquetting Coals.

pressing pressure 400 kg/cm^2 . The shape of briquettes is shown on the photograph. Changes on storing of the properties of the binders used are shown in Table 4, and changes in the mechanical properties of briquettes on storing, in Table 5. The quality of briquettes was good; they ignite at 900°C , initially with a smokey flame and then with a colourless flame. There are 1 figure, 5 tables and 2 Slavic references.

ASSOCIATION: UKhIN

AVAILABLE: Library of Congress

Card 2/2

STEPANENKO, M. A.

68-7-11/16

AUTHORS: Stepanenko, M.A., Matusyak, N.I. (UKhIN), Kuleshov, P.Ya., and Saltan, P.L.

TITLE: Intensification of the Process of Production of High Melting Pitch. (Intensifikatsiya protsessa polucheniya vysokoplavkogo peka).

PERIODICAL: Koks i Khimiya, 1957, Nr 7, pp.43-46 (USSR)

ABSTRACT: The use of oxygen for the intensification of the process of production of high melting pitch was investigated on a laboratory and works' scale. The comparison of laboratory experiments of blowing medium pitch, pitch tar and their mixture (75% + 25% respectively) with air and oxygen is given in Table 1 and Fig.1. When blowing with oxygen (18 l/hr per kg of pitch) the waste gas contained about 60 to 70% of oxygen. Better utilisation of oxygen was obtained when additional mechanical stirring was applied, so that oxygen consumption was reduced to 6 l/hr per kg of pitch per hr (Table 2). Industrial experiments were carried out in two continuously operating reactors joined in series. Dimension of the reactor: $d = 3$ m; h total 4.7 m, the ratio of h pitch to $d = 1.6$; charge 59 tons. The comparison of results obtained in laboratory and works' experiments is given in Table 3. It was found that by replacing air with oxygen,

Card
1/2

68-7-11/16

Intensification of the Process of Production of High Melting Pitch.

the reaction time and the total oxygen consumption can be decreased by 2.5 - 3.0 times (at similar blowing velocities), or the reaction time can be decreased by 1.5 - 2.0 times with a decrease in the total consumption of oxygen by 6-7 times (in comparison with air). In the latter case the use of mechanical stirring is necessary. In considering the most suitable type of apparatus for blowing oxygen it is stated that a bubbler type reactor is the most suitable. There are 3 tables and 2 figures.

ASSOCIATION: Zaporozhskiy Coke Oven Works. (Zaporozhskiy Koksokhimi-cheskiy Zavod).

AVAILABLE: Library of Congress
Card 2/2

PERIODICAL: KOKS I KHEMIYA, 1977, No. 2, pp. 11-13

ABSTRACT: Laboratory experiments on the production of pitch with high softening temperatures are described. It was possible to obtain two types of pitch: (a) pitch with a softening temperature considerably above 1500°C but fluid at high temperatures and (b) pitch with a softening temperature of 18-20% high melting temperature and remaining solid at 300°C. For the production of the latter type of pitch mechanical agitation was found to be necessary. The apparatus used is shown in Fig.1; experimental conditions in Table 2; properties of pitches obtained and their elemental composition in Tables 2 and 3 respectively; the evolution of gas on coking of high softening pitch in Figs. 2 and 3; plastometric properties of pitch with volatile content of 18.5% in Fig.4. There are 3 tables and 4 figures.

ASSOCIATION: UKhIN.

AVAILABLE: Library of Congress.
Card 1/1

68-58-2-5/21

AUTHORS: Stepanenko, M.A., Soldatenko, Ye.M., Matusyak, N.I.
and Bogoyavlenskiy, K.A.

TITLE: X-ray Analysis of Pitch Cokes (Rentgenostrukturnyy
analiz pekovykh koksov)

PERIODICAL: Koks i Khimiya, 1958, Nr 2, pp 31 - 35 (USSR)

ABSTRACT: Results of X-ray structural investigations of pitch cokes from Zaporozhe, Khanzhenskoy and Kemerovsk Coke Oven Works are described. In the evaluation of pitch coke as a raw material for the electrode industry, the most important is not so much its initial characteristics, but the dynamics of changes of the individual indices on thermal treatment and in particular the ability to increase the density. Therefore, not only initial samples were studied, but also samples which were submitted to ignition and graphitisation in industrial furnaces of the Dneprovsk Electrode Works. In addition to parameters of X-ray structural analysis, as indices characterising the coke substance and its structure, the chemical composition, specific gravity and specific electrical conductivity were determined. Copper radiation with a nickel filter was used for X-ray powder photographs. As a criterion of the degree of order, the sizes of "packets" along c and a axis were taken, i.e. the width of interference bands (002) and (10)

Card 1/2

X-ray Analysis of Pitch Cokes

68-58-2-5/21

The results obtained are assembled in the table.
There are 2 figures, 1 table and 7 Soviet references.

ASSOCIATION: UKhIN

AVAILABLE: Library of Congress

Card 2/2

- | | |
|--------------------------|-------------------------------|
| 1. Coke - Properties | 2. Coke - Structural analysis |
| 3. Coke - X-ray analysis | 4. X-rays - Applications |

SOV/68-59-4-13/23

AUTHORS: Gogoleva, T.Ya. and Stepanenko, H.A.

TITLE: Surface Tension, Density and Viscosity of Coal Tar Pitch
(Poverkhnostnoye natyazheniye, plotnost' i vyazkost'
kamennougol'nogo peka)

PERIODICAL: Koks i Khimiya, 1959, Nr 4, pp 42-45 (USSR)

ABSTRACT: An investigation of the above properties of coal tar pitches at elevated temperatures produced on the Zaporozh'ye Works has been carried out. The characteristic data on pitches investigated are given in table 1 and the results obtained in table 2 and figures 3-6. The apparatus used for the determination of surface tension and viscosity are shown in Fig 1 and 2 respectively. It was found that the temperature-density relationship in the region of high temperatures (180 to 360°C) is linear. Coefficients of thermal expansion of pitches with softening temperatures 65, 83 and 145°C were calculated and the dependence of the above coefficients on the softening temperature of pitch was determined (an increase of the softening temperature by 1° is accompanied by a decrease in the coefficient of thermal

Card 1/2

SOV/68-59-4-13/23

Surface Tension, Density and Viscosity of Coal Tar Pitch

expansion by 0.000001). The viscosity of medium pitches within the temperature range 155 to 295°C and of high softening pitch in the range of 240 to 345°C was determined (Fig 5). The dynamics of changes in the viscosity of pitch with increasing heating temperature were studied. Two regions of a sharp change in the viscosity of pitch were observed: one on passing from the solid state into the plastic state and the other on passing from plastic state into the fluid state (Fig 6). There are 6 figures and 2 tables.

ASSOCIATION: UKhIN

Card 2/2

GOGOLEVA, T. Ya., STEPANENKO, M.A.

Thermography of the coking process of coal-tar pitches. Koks i
khim. no.3:47-51 '60. (MIRA 13:6)

1. Ukrainskiy uglekhimicheskiy institut.
(Pitch)

STEPANENKO, M.A.; MATUSYAK, N.I.

Physicochemical properties of pitch coke. Koks i khim. no.6:28-
31 '60. (MIRA 13:7)

1. Ukrainskiy uglekhimicheskiy institut.
(Coke)

STEPANENKO, Mariya Aleksandrovna; BRON, Yakov Abramovich; KULAKOV,
Nikolay Konstantinovich; LEYTES, V.A., otv.red.;
LIBERMAN, S.S., red.izd-va; ANDREYEV, S.P., tekhn.red.

[Production of pitch coke] Proizvodstvo pekovogo koksa.
Khar'kov, Gos.nauchno-tekhn.izd-vo lit-ry po cherno i
tsvetnoi metallurgii, 1961. 311 p. (MIRA 14:7)
(Coke industry—Equipment and supplies]

STEPANENKO, M.A.; MATUSYAK, N.I.

Physicochemical characteristics of coal pitch coke. Koks i khim.
no.1:29-33 '63. (MIRA 16:2)

1. Ukrainskiy uglekhimicheskiy institut.
(Coke—Testing)

STEPANENKO, M.A.; GOGOLEVA, T.Ya.

Uses of coal-oil pitch. Koks i khim. no.12:43-45 '63.
(MIRA 17:1)

1. Ukrainskiy uglekhimicheskiy institut.

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z 0 1 2 3 4 5 6 7 8 9																									
1st AND 2nd LETTER													3rd AND 4th LETTER												
AUTHOR INDEX													SUBJECT INDEX												
METALLURGICAL LITERATURE CLASSIFICATION																									
<p> Stepanenko, M. G., Galkin, P. I., and Korchagin, A. A. EXPERIMENT ON THE USE OF RUSSIAN QUARTZITES FOR THE MANUFACTURE OF DINAS. Trans. Inst. Hlg. Ma- terials & Glass, Vol. 33. State Technical Publishing House, Moscow, 1930. 27 pp. Price 65 kopeks. Re- viewed in <i>Glastek. Rev.</i>, 9 [1] 54 (1931).—Quartzites for Dinas are of two groups: cementless and rich in cement. The first group is characterized, usually, by coarse quartz grains having a small content of amorphous quartz (glass) as a cementing medium. The other group is erroneously called amorphous and differs in the size of the grains and in the cementing glass. The geological origin and history of each group are given. The fine crystalline quartzite, rich in cement, trisymmetrizes much easier and does not ex- pand later. First-grade Dinas can be made from coarse crystalline quartzites by special firing. The quartzites of Kursk should be considered as chakidony sandstones and those of Ural as cementless, more fine-grained than those of Kursk. </p>																									
1st AND 2nd LETTER																									
3rd AND 4th LETTER													5th AND 6th LETTER												

DUP																										1 U OTH																										31 32 33 34 35 36 37 38 39 40 41 42 43 44 45																										17 ON AT IS TS																									
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z																										A B C D E F G H I J K L M N O P Q R S T U V W X Y Z																										A B C D E F G H I J K L M N O P Q R S T U V W X Y Z																										A B C D E F G H I J K L M N O P Q R S T U V W X Y Z																									
1ST AND 2ND LETTER																										2ND LETTER																										3RD AND 4TH CIPHERS																										7- GROUPS																									
AUTHOR INDEX																																																																														MATERIALS INDEX																									
2-2																																																																														A 13-13A METALLURGICAL LITERATURE CLASSIFICATION																									
<p><i>R</i></p> <p>Kuzmich, B. F., and Stepanenko, M. G. CORROSION OF GLASS FURNACE BLOCKS. <i>Kerám. i Staklo</i>, 10 (6) 22-28; [7] 24-28 (1934).—Details are given of examinations of several glass tank furnaces and of the degree of corrosion of the blocks.</p>																																																																																																							
131825 WIP GHW dat																										131825 WIP GHW dat																										131825 WIP GHW dat																										131825 WIP GHW dat																									

A combination furnace for glass manufacture. M. S. Stepanov, L. K. Kovalev and R. M. Polik. *Keram. i Staklo* 1959, No. 3, 31 p; *Khim. Recl. Zue. 2, No. 1, 122 (1959)*. — Expts. on a semi-plant scale are described. The combination system combines the work of the shaft furnace and the bath furnace. In the shaft furnace fusion and glass formation take place; in the bath furnace degassing and homogenization occur. The usual reservoir of the glass-producing furnace is omitted by means of a sloping duct to a shaft. Production is increased by this combination arrangement. W. R. Himm

W. R. Brown

A 50 36 A METALLURGICAL LITERATURE CLASSIFICATION

PROCESSES AND PROPERTIES INDEX																																																																													
1ST AND 2ND CODES													3RD AND 4TH CODES																																																																
<p>C</p> <p>Consumption of fuel in Fourcrault tank furnaces using sulfate charges. M. G. STEPANENKO AND A. A. SOKOLOV. <i>Nedol'maya i Keram. Prom.</i>, 1945, No. 4-5, pp. 38. -- Calculations are given for the following cases: (1) melting of glass from a soda charge, (2) melting of glass from a sulfate charge, and (3) melting in a furnace with a worn lining (toward the end of operations). The effect of moisture in the fuel on fuel consumption, variations in fuel consumption when melting sulfate charge, and hydraulic conditions in the furnace under various operating conditions are also discussed. B. Z. K.</p>																																																																													
METALLURGICAL LITERATURE CLASSIFICATION																																																																													
<table border="1"> <tr> <td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td><td>14</td><td>15</td><td>16</td><td>17</td><td>18</td><td>19</td><td>20</td><td>21</td><td>22</td><td>23</td><td>24</td><td>25</td><td>26</td> </tr> <tr> <td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td> </tr> </table>																										1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26																										
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26																																																				

Differential melting of glass and its application in practice. L. K. KOVALYK AND M. G. STEPANENKO. *Szhekol'naya i Keram. Prom.*, 1947, No. 2, pp. 7-9. Since 1937 research has been carried on at the Moscow Technological Institute of Light Industry and at the Institute of Glass for the purpose of radically changing the process of glassmelting and the construction of the glassmelting furnace by decreasing the melting section. As a result of this work two shaft-forechamber units have been put into operation. These are based on the differential melting of the glass involving the preliminary treatment of the charge first in the shaft and then in the forechamber from which the molten mass at 1250° to 1320° C. is passed into the melting section of the furnace. In this process the primary stage of glassmelting with all its undesirable consequences is eliminated from the glassmelting furnace. By utilizing the heat of the tank furnace and by exhausting part of the furnace gases through the forechamber and the shaft to heat the moving charge, the thermal efficiency of the whole unit is raised. This also makes it possible to regulate the gas medium over the charge and to vary the partial pressure therein. The unit

is designed to operate under the most unfavorable conditions, such as the use of a sulfate charge, high moisture content in the charge, and the use of wood shavings as a reducing agent. Ordinarily, two units are installed with each tank furnace; the number depends on the composition of the charge, the desired output, and the width of the furnace. The use of one of these units with a tank furnace which was equipped with one Fourcault machine raised the output from 12 to 14 tons per 24 hr to 17 to 18 tons. These units can work with only one charge, not requiring the usual additions of cullet. The homogeneity of the glass was not affected by the installation of these units.

B. Z. K.

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

1ST AND 2ND ORDERS																										3RD AND 4TH ORDERS																									
PROCESSES AND PROPERTIES INDEX																																																			
<p>Efficiency of glassmelting furnaces of the type SKP. M. G. STEPANENKO AND I. O. TOMASHEVICH. <i>Steklo i Azbest</i>, 5 [1] 8-13 (1948).—In the SKP furnace, only the glass formation proceeds in a tank, while all preliminary stages are transferred to a shaft forechamber in which the charge moves down an inclined bottom toward the tank and is heated by radiant heat from the tank and by a greater portion of the furnace gases. Approximate calculations indicate that the SKP system has more economical utilization of heat than an ordinary tank furnace (for the same output). In addition, this system gives greater output of the furnace at normal temperature conditions. B.Z.K.</p>																																																			
<p>ASS-SLA METALLURGICAL LITERATURE CLASSIFICATION</p>																																																			
<p>1ST AND 2ND ORDERS</p>																																																			

PROCESSES AND PROPERTIES INDEX																									
19																									
CA																									
<p>Some results of work with the "SKP" combination furnace. M. G. Stepanenko and I. O. Tomashevich. <i>Leg. kays Prom.</i> 8, No. 5, 1948; cf. C.A. 43, 1530g. Larger models of the "SKP" furnace, having glass-melting tank dimensions in excess of 100 sq. m., have been constructed recently. Compos. of a typical product was: SiO_2 71.23, R_2O_3 0.5, CaO 7.45, MgO 4.57, Na_2O 16.74, and SO_2 0.50%.</p> <p>Marshall Sittig</p>																									
<p>ASSOCIATED METALLURGICAL LITERATURE CLASSIFICATION</p> <p>1948-1950</p> <p>1951-1955</p> <p>1956-1960</p> <p>1961-1965</p> <p>1966-1970</p> <p>1971-1975</p> <p>1976-1980</p> <p>1981-1985</p> <p>1986-1990</p> <p>1991-1995</p> <p>1996-1999</p>																									

STEPANENKO, M. G.

Electric heating of glass in the Foureault channel. G. M. Ashkinazi, E. V. Zhukorskii, and M. G. Stepanenko. Steklo i Keram., 6 (3) 3-9 (1949).
--Electric heating was undertaken to combat streaks and devitrification. The electrodes (3-in. steel tubes) were immersed to a depth of 20cm. It was possible to attain complete isothermy of the melt under the debiteuse, with a total rise in temperature in this zone of 30°. Temperature distribution along the depth of the melt in the preheating chambers was considerably improved. Temperature difference between the surface and a depth of 55 cm. was reduced from 160° (original temperature) to 110°C. Equalization of temperature was caused by a 15° to 20° drop in the upper levels and a 30° to 40° rise at a depth of 30 to 55 cm. At a depth of 55 cm., the temperature rose from 990° to 1030°, thus eliminating the possibility of crystallization. Devitrification was completely eliminated, and streaks were considerably reduced. Temperature curves and a schematic diagram of the electrical system are given.

B.Z.K.

CA

19

Rational dimensions of tank-furnace regenerators.
M. G. Gerasimov. *Stal' : Krasn. 7, No. 1, 5-6 (1950).*—
Math. analysis of operation and limitations of regenerators
for tank furnaces using generator gas of 1000-1800 cal./m.³.
With gas of 1800 cal./m.³, heating temps. higher than 1180°
should not be expected; under ordinary conditions, with
gas of 1100-1300 cal./m.³, the temp. of air (and gas)
will not exceed 950-1000°. The specific surface of the re-
generator should be 33-6 m.²/sq. m. of surface being
heated (this was 116 m.² in these calcs.). B. Z. K.

PROCESSING AND PROPERTIES INDEX	
<p>Improving the optics of sheet glass by electric heating of the melt. M. G. STEPANENKO, G. M. ASHIGIN, AND L. V. CHERN- VATENKO. <i>Steklo i Keram.</i>, 7 (2) 3-6 (1950). Electric heating of the melt for one month at the Proletari glassworks resulted in a reduction of streaks and devitrification. The optimum condi- tions are 55 to 65 v. at the electrodes and a current strength of 140 to 180 amp. The electric heating lowered the temperature gradient in the melt along the width and depth of the canal from 20° to 2-3°, and the temperature in the depth of the melt in the working canal rose 35° to 40°. The most advantageous distri- bution of the electrodes is directly before the bridgewall in the working chambers for both direct and consecutive feeding of the melt. The heads of the electrodes, 100 mm. in diameter, are immersed to a depth of 300 to 350 mm. from the surface and 200 mm. from the inner wall of the canal. The consumption of elec- tric energy is about 10 kw.-hr. per 100 sq m. of glass. Tempera- ture curves with and without electric heating are given. Cf <i>Ceram. Abstracts</i>, 1950, July, p. 140b. H Z K.</p>	
<p>ASB-51A METALLURGICAL LITERATURE CLASSIFICATION</p>	
<p>STANDARD</p>	<p>STANDARD</p>

EYGENSON, L.S., doktor tekhnicheskikh nauk, professor; STEPANENKO, M.G., redaktor; GRIBOVA, M.P., tekhnicheskiiy redaktor.

[Making models] Modelirovanie. Moskva, Gos.izd-vo "Sovetskaya nauka,"
1952. 371 p. (MLRA 8:5)
(Engineering models)

STEPANENKO, M.G., professor, doktor tekhnicheskikh nauk

Importance of the convection flow in glass furnaces. Stek.i ker.
12 no.9:17-22 S'55. (MIRA 8:12)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut stekla
(Glass manufacture)

STEPANENKO, M.G., doktor tekhnicheskikh nauk, professor.

Design of a glass tank furnace. Stek. 1 ker. 13 no.9:27-28
S '56.

(MLRA 9:10)

(Glass manufacture)

8 (4)

SOV/112-57-5-10448

Translation from: Referativnyy zhurnal. Elektrotehnika, 1957, Nr 5, p 131 (USSR)

AUTHOR: Stepanenko, M. G., Lur'ye, V. M.

TITLE: Design of Electric Glass-Melting Furnaces
(Proyektirovaniye elektricheskikh steklovarenykh pechey)

PERIODICAL: Tr. Vses. n.-i. in-ta stekla, 1956, Nr 36, pp 51-70

ABSTRACT: Electric glass-melting furnaces have a number of advantages compared to flame-type furnaces; it is expected that in the near future, when new large electric stations will be put in operation, such furnaces will receive wide usage in the USSR. At present, however, the problems of design and construction of glass-melting furnaces have not been satisfactorily solved, either in the USSR or abroad. In designing electric glass-melting furnaces, their fundamental parameters are selected after those of the flame-type furnaces, or else they are selected arbitrarily. As a result, the per-unit energy consumption of actual electric furnaces fluctuates widely. The prospects of electric glass melting require that reliable methods for designing

Card 1/4

SOV/112-57-5-10448

Design of Electric Glass-Melting Furnaces

the furnaces be developed, particularly methods for furnaces of 80-120 tons per day capacity. The principal distinguishing feature of electric glass melting is that heat is produced within the glass melt proper; the heat is not transmitted via the glass-melt surface as in the flame-type furnaces. This results in a more uniform temperature distribution over the entire glass-melt volume, and in lower maximum temperatures at individual points; the temperature under the furnace roof does not exceed $1,250^{\circ}\text{C}$, which results in a higher electrode and lining durability. The process in an electric furnace can be forced by using higher glass-melt temperatures. Horizontal convection in an electric furnace is weak, and the furnace outlet requires additional heating. The glass-melt surface in the electric furnace is a cooling surface, hence the viscosity of the surface layers is higher. This can be prevented by a lower roof, by coating the surface with a special mixture, by a vacuum, and by placing high-capacity electrodes near the surface. Decreasing the surface area and making the bath deeper did not result in a decrease of heat losses

Card 2/4

SOV/112-57-5-10448

Design of Electric Glass-Melting Furnaces

through the surface because the losses through the walls increased. An operating voltage of 70-110 v is used; it can be increased to 220 v. The bath width must be limited in order to limit the voltage. As glass melt is electrically hot, workers and glass-forming machines that come in contact with the glass melt must be insulated from the ground. Usually the single-phase type of electric furnace is used. The most expedient surface configuration is a long rectangle. Attempts to construct a 3-phase furnace have been unsuccessful so far. The construction of an electric glass-melting furnace is much simpler than that of a flame-type; the electric furnaces are usually protected by a metal housing. Three types of electrodes are used; the wall type, the through type, and the semi-through type. The electrodes are made from a graphitized carbon or from high-melting metals. The latter require compressed-air cooling, which lowers their efficiency. With through-type electrodes, the temperature and current-density distribution over the glass melt is nonuniform because of different cooling conditions at various spots of

Card 3/4

SOV/112-57-5-10448

Design of Electric Glass-Melting Furnaces

the melt. Wall-type graphitized electrodes are the best. Thermal and electrical calculations of an electric glass-melting furnace are difficult, and in practice the required power is determined on the basis of the bath volume. The design methods for a single phase wall-electrode furnace suggested by the authors permit determining its fundamental parameters with sufficient accuracy, except for the calculated resistivity at various spots of the melt, which is associated with the distribution of working temperatures. Capacity per unit volume and energy consumption per ton of the glass produced are two most characteristic performance data.

V.P.Kh.

Card 4/4

AUTHOR: Stepanenko, M. G.

SOV/72-56-9-4/17

TITLE: Nomogram for the Determination of the Specific Heat Consumption in Glass Melting (Nomogramma dlya opredeleniya udel'nogo raskhoda tepla na varku stekla)

PERIODICAL: Steklo i keramika, 1958, Nr 8, pp. 8-12 (USSR)

ABSTRACT: The thermal parameters of the thermochemical reactions of glass melting have been known for a long time and were published by M. A. Matveyev, B. A. Kleymenov (Ref 1) as well as by Krüger (Ref 2) in technical literature. Also Kuzyak, Sukhov (Ref 2) and Professor Ginzburg (Ref 3) carried out research work in this field and obtained higher parameter values. The author prefers the data supplied by Krüger as his conceptions coincide with those by Professor M. A. Bezborodov, I. D. Tykachinskiy and others, and he constructs the nomogram on the basis of his data. (See table). Temperatures of 1450-1500° were assumed as to dominate in the practice of industrial glass melting (Table 1). For the calculation of the specific heat consumption that temperature is taken as heating temperature at which the glass mass is

Card 1/3

SOV/72-58-8-4/17

Nomogram for the Determination of the Specific Heat Consumption in Glass Melting

entering the cooling and working zone. The influence of the factors - the ratio between charge and broken glass, as well as the humidity content of the charge - are described in detail. The elaborated nomogram (see figure) consists of 6 fields and takes into account the ratio between soda and sulfate, the humidity content of the charge, the maximum furnace temperature, the heating of the charge gases, the amount of broken glass and the correction for sodium sulfate. A number of published calculations of the heat consumption in the melting of 1 kg metal is mentioned (Table 2). Then the utilization of the nomogram is described and illustrated by examples. In table 3 the recalculation results carried out by means of the nomogram of earlier published values of the specific heat consumption in the melting of various kinds of glass is mentioned. By means of this nomogram the exact values of the specific heat consumption can be obtained on different conditions. This way the degree of the efficiency of various ash furnaces can be compared. There are 1 figure, 4 tables, and 8 references, 5 of which are omitted.

Card 2/3

Nomogram for the Determination of the Specific Heat Consumption in Glass Melting SOV/72-58-8-4/17

1. Glass--Melting
2. Heat--Measurement
3. Nomographs--Preparation

Card 3/3

AUTHOR: Stepanenko, M. G. SOV/72-58-9-1/20

TITLE: The Efficiency of Glass Melting Tank Furnaces (Koeffitsiyent poleznogo deystviya vannyykh steklovarenykh pechey)

PERIODICAL: Steklo i keramika, 1958, Nr 9, pp 1 - 3 (USSR)

ABSTRACT: The efficiency of pot and tank furnaces is usually computed according to the following formula

$$\eta = \frac{Q_{\text{utilized}}}{Q_{\text{applied}}} \cdot 100 \text{ where } Q_{\text{applied}} \text{ denotes the entire}$$

heat content of the fuel burned in the furnace, and Q_{utilized} denotes the amount of heat required for the melting of the batch. For the computation of Q_{utilized} no customary method is established. Hence the results obtained by different authors vary, as it is corroborated by the papers by V.A.Kuzyak, A.A.Sukhov, D.B.Ginzburg and M.G.Stepanenko (Ref 1). The Soviet scientists V.G.Gutop, D.B.Ginzburg as well as foreign ones found that the conception of Q_{utilized} as denoting only the

Card 1/3

The Efficiency of Glass Melting Tank Furnaces

SOV/72-58-9-1/20

amount of heat required for the melting of the glass is erroneous. They, however, abstained from giving a precise definition of this quantity and thus did not make possible a determination of the true value of the efficiency η . According to Professor I.I.Kitaygorodskiy (Ref 1) the reaction of glass formation of commercial glass types proceeds according to information given in the table. It can be seen that the de-gasification of the melt requires higher temperatures than the melting process proper. The amount of heat consumed in that process must be added to the quantity of Q utilized.

Thus the efficiency of the furnace is increased as can be seen from the figure. The computation of the heat required for the de-gasification meets with difficulties. On the basis of data published by a number of authors (Maurakh, Udovenko, Ginzburg, Kuzyak, Sukhov) the heat required for de-gasification can be assumed to amount to 50% of the heat of melting. Experiments carried out by the Institut ispol'zovaniya gaza AN USSR (Institute of Gas Utilization AS USSR) and by the Teplotekhnicheskaya laboratoriya GIS (Heat Engineering Laboratory GIS) yielded

Card 2/3

The Efficiency of Glass Melting Tank Furnaces

SOV/72-58-9-1/2c

the same results. A separate heating of the fining zone permits to reduce the heat consumption. Investigations of furnaces in operation permit to design perfected types of furnaces, in which the melting and the fining zone are run under optimum conditions. The values of Q utilized computed in this way will permit to compare the advantages of different furnace processes in a correct manner and to pass an accurate judgement on them. There are 1 figure, 1 table, and 8 references, 5 of which are Soviet.

ASSOCIATION: Gosudarstvennyy nauchno-issledovatel'skiy institut stekla
(State Scientific Research Institute of Glass)

Card 3/3

AUTHORS: Krechmar, V. A., Stepanenko, M. G. SOV/72-58-10-7/18

TITLE: Influence Exerted by Gas Density of the Bricking of the Regenerative System of Glass-Melting Furnaces Upon Their Efficiency (Vliyaniye gazoplotnosti kladki regenerativnoy sistemy steklovarenykh pechey na ikh koeffitsiyent poleznogo deystviya)

PERIODICAL: Steklo i keramika, 1958, Nr 10, pp 28-30 (USSR)

ABSTRACT: Teploekhnicheskaya laboratoriya Instituta stekla (Thermal Engineering Laboratory of the Glass Institute) investigated within the last two years a number of glass-melting tank furnaces for the manufacture of sheet-glass. It was found that by premature combustion of gas, by sucking of air of untight bricking the heating power of the gas is reduced by 8-17 %. On the basis of numerous analyses of the composition of generator gas in tank furnaces of the plants Lisichansk, Gor'kiy, Konstantinovka imeni Oktyabr'skaya revolyutsiya the diagram (Fig 1) was established from which the heating power of the gas in the individual cases can be determined. Figure 2 shows the dependence of the burning temperature upon the quantity of excess air in the use of purified gas

Card 1/2

SOV/72-58-10-7/18

Influence Exerted by Gas Density of the Bricking of the Regenerative System of Glass-Melting Furnaces Upon Their Efficiency

in Gor'kovskiy stekol'nyy zavod (Gor'kiy Glass Works.) as well as of gas not purified in Bytoshevskiy stekol'nyy zavod (Bytosh Glass Works). In order to obtain a certain temperature level in the furnace, more gas must be added, thus increasing the fuel consumption (Fig 3). These deficiencies were observed in all furnaces examined by the Glass Institute. In order to eliminate these deficiencies it is necessary to seal the joints in the brick work as described in the papers of Nokhratyan. At present, D. B. Ginzburg, M. A. Matveyev (MKhTI) are carrying out experiments with a new sealing plaster in the plant ~~in~~ Gor'kiy. The fuel consumption of the furnace is reduced by sealing of the walls, thus increasing the output of the furnace considerably. There are 3 figures.

Card 2/2

15(2)

AUTHOR:

Stepanenko, M. G.

SOV/72-58-12-3/23

TITLE:

Gas-Electric Tank Furnaces for Glass Melting (Gazo-
elektricheskiye steklovarennyye vannyye pechi)

PERIODICAL:

Steklo i keramika, 1958, Nr 12, pp 8 - 13 (USSR)

ABSTRACT:

As an example of such installations, the author describes the furnaces of the Karkula factory (Finland), featuring a combined oil and electric heating system. (Figs 1,2 and 3). The latter is effected by means of special air atomizers and molybdenum electrodes. The working temperature of the furnaces amounts to 1530 - 1550° (crystallizing range) and 1450° (feeding range). Figures 4 and 5 show the arrangement of the electrodes. Further, the fuel consumption in the furnaces and the current density of the electrodes are indicated and described as being too high for molybdenum electrodes, according to the paper by E.V.Borel' (Ref 1). In figure 6 the electrodes are distributed in such a way as to secure their symmetrical performance; the author assumes the

Card 1/3

Gas-Electric Tank Furnaces for Glass Melting

SOV/72-58-12-3/23

operation of the electrodes to be individually controlled. The table shows the specific heat consumption, depending on the specific output at a tank surface of 20 m^2 ; in figure 7 this dependence is represented graphically. In conclusion the author states that gas-electric furnaces represent a progressive furnace type and that it would be therefore useful to adopt them in the glass industry of the USSR for the manufacturing of piece products. The construction of such furnaces must be sped up in the Moldavskaya SSR. At the Gor'kovskiy stekol'nyy zavod (Gor'kovskiy glassworks) the changing over of a large furnace producing 140-160 t sheet glass a day to the gas-electric heating system is to be effected. As no experience in this connection has yet been made, the performance of these furnaces is to be thoroughly investigated, in order to obtain the prerequisites for the quickest possible charging over of other sheet glass producing furnaces. Measures must also be taken, in order to secure the production of molybdenum electrodes in the USSR. There are 7 figures, 1 table and 1 Soviet

Card 2/3

Gas-Electric Tank Furnaces for Glass Melting
reference.

SOV/72-58-12-3/23

Card 3/3

STEPANENKO, M. G.

50V/72-58-12-21,23

 $25(9) - 25(5)$

None Given

1712

104M W F 12. DP 45-46 (DSSA)

ABSTRACT

[illegible]

5/1 PROJ

Corbett

[illegible]

cord's

VILNIS, K.K.; POLLYAK, V.V.; STEPANENKO, M.G.

Most satisfactory temperature conditions for the melting end of
glass tank furnaces. Stek. i ker. 15 no.4:1-5 Ap '58. (MIRA 11:5)

1. Institut stekla.

(Glass furnaces)

SOV/72-59-3-3/19

15(2), 15(6)
AUTHORS:

Vilnis, K. K., Stepanenko, M. G.

TITLE:

Heat Exchange Between the Charge and the Hearth of the Glass Melting Furnace (Teploobmen mezhdur shikhtoy i plamennym prostranstvom steklovarennoy pechi)

PERIODICAL:

Steklo i keramika, 1959, Nr 3, pp 8 - 11 (USSR)

ABSTRACT:

The authors state that data contained in publications are very contradictory with respect to the dependence of the melting rate of glass as well as the furnace efficiency on temperature (Figs 1 and 2), and are therefore not a reliable basis for the intensification of the melting process in tank furnaces. Relatively few investigations have so far been carried out in the field of heat exchange research (D. B. Ginzburg, Ref 1). The present paper offers an explanation of heat exchange between the upper furnace structure, the charge, and the charge foam in the melting region, basing on K. K. Vilnis' paper (Ref 2). Figure 3 shows the dependence of temperature of the charge surface on the magnitude of

Card 1/2

Heat Exchange Between the Charge and the Hearth of the
Glass Melting Furnace

SOV/72-59-3-3/19

the heat current flowing onto it, and figure 4 depicts the heat amount absorbed by the charge. Figure 5 gives the variations of temperature in every point of the charge surface. The heat amount absorbed by the melting zone depends, firstly, on the ratio of the areas occupied by the charge and the charge foam, and secondly, on the magnitude of the absolute temperature in the upper structure. The efficiency increase of tank furnaces for glass melting is not only brought about by providing high temperatures, but also by the rational exploitation of the heat exchange both in the gas zone and in the glass mass. Further accurate investigations are required for this purpose. There are 5 figures and 4 references, 3 of which are Soviet.

Card 2/2

15(2)

AUTHORS:

Stepanenko, M. G., Pavlov, V. S.

SOV/72-59-4-2/21

TITLE:

On the Effect of a Blocking Device on the Thermal Balance of the Cooling Part of a Tank Furnace (Vliyaniye zagraditel'nogo ustroystva na teplovoy balans studochnoy chasti vannoy pechi)

PERIODICAL:

Steklo i keramika, 1959, Nr 4, pp 6-11 (USSR)

ABSTRACT:

For the purpose of increasing the specific output of metal, the melting temperature of the furnace must be increased. Since the working temperature of the glass mass must, however, remain unchanged in this case, the processing part of the furnace had to be screened off. However, it was found in this connection that the temperature of the flow of the glass mass to be processed was considerably lower. Since nothing else had been changed in the design of the furnace this could only be explained by the introduction of the lower colder glass mass into the flow to be processed which was confirmed by temperature measurements performed by the teplotekhnicheskaya laboratoriya Instituta stekla (Heat Engineering Laboratory of the Glass Institute) and foreign investigations (Ref 1). This might, however, cause deterioration of the quality of the glass mass. For this reason, investigations had to be carried

Card 1/3

On the Effect of a Blocking Device on the Thermal
Balance of the Cooling Part of a Tank Furnace

SOV/72-59-4-2/21

out in order to find a design of screening which would guarantee an increased output of glass mass without a deterioration of the quality. In figures 1,2,3, and 4 the different types of furnaces with and without shuttle are shown and discussed. The velocity of the upper layer of the glass mass was determined by using floats and the amount of the convection currents by using the A. A. Sokolov formula (Ref 2). In table 1 the technical and operational characteristics of the furnaces investigated are given and table 2 gives the thermal balances of the cooling parts of the tank furnaces. In table 3 the balance of the glass mass in the range of the blocking devices of the furnaces is given. Maximum specific temperature drops may be observed in tanks with deeply immersed shuttles and low screens. This explains the opinions expressed by I. I. Tikh and M. B. Epel'baum (Ref 3). In table 4 the thermal balances of the flow to be processed in the range of the screening device of the furnaces investigated are given. Figure 5 shows the dependence of the output of first-quality glass on the coefficient of the introduction of the metal. The investigations carried out of the furnace output as well as the operational

Card 2/3

On the Effect of a Blocking Device on the Thermal
Balance of the Cooling Part of a Tank Furnace

SOV/72-59-4-2/21

and technical values are considered to be a beginning of the investigations of a screening device which makes it possible to find an optimum design and optimum operational conditions for increasing the fusibility of the tank furnaces without risks. The influence exercised by the blocking device on the quality of the production must also be thoroughly investigated. There are 5 figures, 4 tables, and 4 references, 3 of which are Soviet.

Card 3/3

PHASE I BOOK EXPLOITATION SOV/5484

Stepanenko, Mikhail Georgiyevich

Puti sovershenstvovaniya vannykh steklovarennnykh pechey (Ways of Improving Vat Glass Furnaces) Moscow, Gosstroyizdat, 1960. 160 p. Errata slip inserted. 2,200 copies printed.

Sponsoring Agency: Gosudarstvennyy nauchno-issledovatel'skiy institut stekla.

Ed. of Publishing House: S. A. Gladysheva; Tech. Ed.: L. A. Gerasimuk.

PURPOSE: This book is intended for glass technologists.

COVERAGE: The book describes reverberatory, electric, and gas-and-electric vat furnaces for the manufacture of glass. Heating methods, fuel supply, heat distribution, heat exchange, work space arrangement, and the effect of partition structures on the operational efficiency of these in large industrial furnaces are discussed. Recommendations are made for improvements in the design and construction of special purpose vat glass furnaces. The
Card 1/3-

Ways of Improving (Cont.)

SOV/5484

author thanks I. O. Tomashevich and V. V. Pollyak, Candidates of Technical Sciences; K. K. Vilnis, Scientific Worker; V. S. Pavlov, Aspirant; and V. D. Soskova, Junior Scientific Worker. There are 84 references: 56 Soviet, 20 German, and 8 English.

TABLE OF CONTENTS:

Introduction	3
Ch. I. Present State of Glass Vat Furnaces in the USSR	5
Ch. II. Vat Furnace as a Technological Unit	9
Ch. III. Glass Furnace as a Heat Exchange Unit	14
Ch. IV. Prospects of Developing and Increasing the Technical and Economic Efficiency of Glass Furnaces	138

Card 2/3

PATRIN, P.A.; inzh.; KISHENEV, V.F.; TSIPENYUK, M.I., inzh.;
VOZNESENSKIY, A.A., kand.tekhn.nauk; SEDOV, V.G.,
IUR'YE, M.S.; STEPANENKO, M.G., prof.

Over-all mechanization and automatization of the heat
treatment of ceramic stones (comment on M.I. Rogovyi's
and D.O. Konovalov's article). Stroi. mat. 6 no.3:25-27
Mr '60. (MIRA 13:6)

1. Severo-Kavkazskaya nauchno-issledovatel'skaya stantsiya
po stroitel'stvu i stroitel'nykh materialam (for Patrin).
2. Zaveduyushchiy laboratoriyey tresta karagandastroymate-
rialy (for Kishenev). 3. Ukgiprostroyaterialy (for
TSipenok). 4. Zaveduyushchiy kafedroy energeticheskogo
oborudovaniya i avtomatiki Rostovskogo inzhenerno-stroitel'-
nogo instituta (for Voznesenskiy). 5. Glavnyy inzhener
instituta Rosstromproyekt (for Sedov). 6. Glavnyy teplo-
tekhnik instituta Rosstromproyekt (for Iur'ye).
(Kilns) (Automatic control)

STEPANENKO, M.G.

"Glass" by N.Kachalov. Reviewed by M.G.Stepanenko. Stek.i ker.
17 no.3:48 Mr '60. (MIRA 13:6)
(Glass manufacture)
(Kachalov, N.)

STEPANENKO, M.G.; PAVLOV, V.S.

Ways of improving the productivity of pot furnaces for plate glass.
Stek.i ker. 18 no.8:12-15 Ag '61. (MIRA 14:8)
(Glass furnaces)

MEHNICH-PETROSYAN, O.P.; SELIMENKO, I.G.

Electrochemical activation of cements. Dokl. AN SSSR 141
no.1:172-175 N '61. (MIRA 14:11)

1. Predstavleno akademikom I.V.Belovym. :
(Cement)
(Electrochemistry)

NOKHRATYAN, Koryun Amazaspovich, kand. tekhn. nauk; STEPANENKO, M.G.,
doktor tekhn. nauk, prof., nauchnyy red.; NAUMOV, M.M., kand.
tekhn. nauk, nauchnyy red.; ROGOVOY, M.I., laureat Gosudarstven-
noy premii, nauchnyy red.; KOSYAKINA, Z.K., red. izd-va; RUDAKOVA,
N.I., tekhn. red.

[Drying and firing in the structural ceramis industry] Sushka i ob-
zhig v promyshlennosti stroitel'noi keramiki. Moskva, Gosstro-
izdat, 1962. 602 p. (MIRA 15:12)
(Ceramics) (Building materials)

STEPANENKO, M.G., doktor tekhn.nauk, prof.; PAVLOV, V.S.

Method of calculating tank glass furnaces with developed working
end arrangements. Stek. i ker. 19 no.3:1-6 Mr '62. (MIRA 15:3)
(Glass furnaces)

STEPANENKO, M.G., doktor tekhn.nauk, prof.; LIFSHITS, A.V., inzh.;
SIMIN, G.F., inzh.

Study of heat exchange in tunnel kilns during the firing of
ceramic wall materials. Stroi.mat. 8 no.7:28-30 JI '62.

(MIRA 15:8)

(Ceramics)

(Kilns)

VILNIS, V.V., dok.; STEPANENKO, M.G., doktor tekhn. nauk [deceased];
KAPLAN, A.Yu., inzh.

Optimal depth of furnaces for dark green glass. Stek. i ker.
21 no.1:9-13 Ja '64. (MIRA 17:8)

1. Institut stekla (for Vilnis, Stepanenko). 2. Krasnodarskiy
stekol'nyy zavod (for Kaplan).

83579

S/056/60/038/005/012/050
B006/B070

24.2120
26.2310

AUTHORS: Koval'skiy, N. G., Podgornyy, I. M., Stepanenko, M. M.

TITLE: Investigation of Fast Electrons in Strong Pulse Discharges

PERIODICAL: Zhurnal eksperimental'noy i teoreticheskoy fiziki, 1960,
Vol. 38, No. 5, pp. 1439-1445

TEXT: At first, the authors describe the experimental arrangement and the method of measurement. The apparatus used was essentially similar to the pulse generator used for earlier investigations. The condenser bank consisted of 12 condensers of the type MM-3/50 (IM-3/50) with a total capacity of 36 μ F. The discharge chamber was of porcelain, and had a length of 1 m and a diameter of 17 cm. During one discharge, the condenser bank supplied up to 45 kv. The discharge chamber was evacuated after each discharge and filled anew with gas (hydrogen, deuterium, or spectrally pure inert gases). The authors (partly in collaboration with others) had observed in earlier studies (Refs. 1-4) the appearance of a hard X-radiation and an acceleration of electrons (up to (300 ± 20) kev for an initial discharge voltage of 40 kv) while investigating controlled

Card 1/4

Investigation of Fast Electrons in Strong
Pulse Discharges

83579
S/056/60/038/005/012/050
B006/B070

thermonuclear reactions. Following these studies, the authors investigated the dependence of the maximum electron energy on the parameters of the discharge. The dependence of the limiting energy in the electron spectrum on the pressure of hydrogen in the discharge chamber (in the range $4 \cdot 10^{-3} \leq p_0 \leq 6 \cdot 10^{-1}$ torr) was determined by means of a magnetic spectrograph, and is shown in Fig. 1. In the range $2 \cdot 10^{-2} \leq p_0 \leq 1.3 \cdot 10^{-1}$ torr the curve shows a high maximum; the peak value of the electron energy is 295 keV. The pressure dependence of the electron energies is analogous to the pressure dependence of neutron yield in discharges in deuterium, but deviates somewhat from the pressure dependence of the intensity of the hard X-radiation. The dependence of the limiting electron energy (E_0) on the initial voltage U_0 was also investigated (for $p_0 = 7 \cdot 10^{-2}$ torr, in H_2). Fig. 2 shows $E_0(U_0)$ in the range $30 \leq U_0 \leq 45$ kv. E_0 steeply rises with U_0 up to $U_0 = 40$ kv, and then falls. Further, E_0 was determined as a function of the strength of an external magnetic field in the range $0 < H < 150$ oe (Fig. 3). E_0 falls from 300 to 150 keV when the magnetic field increases from 0 to 30 oe; with a further increase of the field, E_0 becomes less

Card 2/4

83579

Investigation of Fast Electrons in Strong
Pulse Discharges

S/056/60/038/005/012/050
B006/B070

than 50 kev. The radial distribution of the fast electrons accelerated along the discharge axis was studied by means of a special collimator schematically shown in Fig. 4. Fig. 5 shows the radial distributions determined for $p_0 = 7 \cdot 10^{-2}$ torr and three different thicknesses of the Al filter (30, 54, and 75μ). Electron energies of 80, 110, and 140 kev, respectively, correspond to these thicknesses. The half width of the distribution curve decreases with increasing thickness of the filter. This shows that the non-equilibrium electron group is accelerated in the immediate neighborhood of the axis. Numerical results of the investigations of fast electrons in H_2 , D_2 , and the inert gases are collected in a table. The investigations led to the conclusion that in high-power pulse discharges there exist two groups of non-equilibrium electrons; the first group having energies of up to 100 kev is accelerated by the electric fields occurring with the pinch effect, while the second group, which has energies of up to 300 kev, is accelerated in the local electric fields resulting from instabilities of the plasma column. The authors thank S. Yu. Luk'yanov for discussions of the results. There are 5 figures, 1 table, and 8 references: 7 Soviet and 1 Italian.

Card 3/4

83579

Investigation of Fast Electrons in Strong
Pulse Discharges

S/056/60/038/005/012/050
B006/B070

ASSOCIATION: Institut yadernoy fiziki Moskovskogo gosudarstvennogo
universiteta (Institute of Nuclear Physics of Moscow State
University) X

SUBMITTED: December 19, 1959

Card 4/4

STEPANENKO, M.N.

USSR/Electronics - Radio station operation

Card 1/1 Pub. 133 - 6/16

Authors : Stepanenko, M. N.

Title : ~~Radio station operation~~
Daily operations in a radio station

Periodical : Vest. svyazi 5, 12-13 May 1955

Abstract : A vivid description is presented of the daily operations and activities in a radio broadcasting station. Operation and maintenance of various radio station equipment is described, and names of some employees are given. Illustrations.

Institution :

Submitted :

6.6/10

KRUK, M.T.; STEPANENKO, M.T.

Testing of a furnace with turbulent composite burners operating
on natural gas by means of a chromatoscope. Energ. i elektrotekh.
prom. no.1:14-18 Ja-Mr '63. (MIRA 16:5)

1. Yuzhnoye otdeleniye Gosudarstvennogo tresta po organizatsii i
ratsionalizatsii rayonnykh elektrostantsiy i setey.
(Furnaces--Testing) (Gas burners--Testing)

POMETUN, G., stolevar; ONISHCHENKO, M., stolevar; STEPANENKO, N., stolevar.

Carrying out the directives of the Congress. Nauka i shizn' 23
no.6:17-19 Je '56. (MLRA 9:9)

1. Ordena Lenina zavoda "Zaporozhstal'."
(Zaporozhye--Steel industry)

ONISHCHENKO, Mikhail Kirillovich, stalevar; POMETUN, Grigoriy Konstantinovich, stalevar; STEPANENKO, Nikolay Aleksandrovich, stalevar; VERETEL'NIK, I.V., inzhener, redaktor; ISLANKINA, T.F., redaktor izdatel'stva; ISLENT'YEVA, P.G., tekhnicheskii redaktor

[Our experience with a rapid oxygen steel making process] Nash opyt skorostnogo stalevarenia s primeneniem kisloroda. Moskva, Izd-vo "Znanie," 1953. 23 p. (Vsesoiuznoe obshchestvo po rasprostraneniю politicheskikh i nauchnykh znani. Ser. 4 no.6) (MIRA 9:7)
[Microfilm]

1. Ordена Lenina zavod "Zaporozhstal'" (for Onishchenko, Pometun, Stepanenko)
(Steel--Metallurgy)

YEREMEYEV, M.N. (Docent) and STEPANENKO, N.D. (Junior Scientific Worker,
All-Union Scientific Research Institute of Animal Raw Material and Fur.)

"The listeriosis disease in sables..."
Veterinariya, Vol. 39, no. 3, March 1962 pp. 57

Determination of moisture in materials by electrical methods. N. N. Serepantko. *Colloid J.* (U. S. S. R.), 3, 449-451 (1937).—The amt. of water in paper contg. up to 15% water can be detd. by measuring the dielec. const. Slight changes in the amt. of impurities with low dielec. const. do not affect the value of the condenser capacity. The method is not sensitive for materials with low moisture content. John E. Ivak

CA

PROCESSES AND PROPERTIES INDEX

Determination of moisture by electric methods. N. N. Stepanenko. *Sbornik Nauch.-Issledovatel. Rabot. Vsesoyuzn. Akad. Pishchev. Prom. im. Stalina 2*, 1961-62 (1963); *Khim. Referat. Zhur.* 1959, No. 8, 63.—The dielec. coeff. of many substances (oil-seed cakes, paper pulp, etc.) depends on their moisture content. Dielec. consts. were measured with a special app. constructed on the principle of resonance. This app. consisted mainly of a high-frequency generator (4×10^4) stabilized with quartz, i. e., the generator operated only when the anodic frequency coincided with the frequency of quartz. Only the capacity was a variable value in the app. The measured capacity was connected in parallel to the main condenser of the generator. At a small content of moisture in samples of press cakes the capacity of the condenser and, therefore, the current in the press cakes increased only slightly, while at a large moisture content a sharp rise of the curve was observed. Results in determ. of the moisture content of paper pulp were excellent and showed a definite relationship between the capacity of the condenser and the amt. of water present. W. R. Henn

ASB-55A METALLURGICAL LITERATURE CLASSIFICATION

1ST AND 2ND CODES										3RD AND 4TH CODES									
PROCESSING AND PROPERTY INDEX																			
<p><i>ca</i></p> <p>Determination of the dipole moments of solutions of fat acids by means of Debye's second method. M. P. Volynovich and N. N. Stepanenko. <i>J. Exptl. Theoret. Phys.</i> (U. S. S. R.) 10, 817-22 (1940). Using a 3.5-meter wave the dielec. consts. and absorption coeffs. were detd. The former vary nearly linearly with the I nos. Dipole moments measured at 2° were: linoleic acid in benzene, $\mu = 1.512$; in toluene, 1.340; oleic acid in benzene, 1.462; stearic acid in chloroform, 1.828; triolein in benzene, 3.124. Cryoscopic measurements indicate that these data refer to the monomeric state. P. H. Rathmann</p>																			
ASS-SLA METALLURGICAL LITERATURE CLASSIFICATION										E-2									
130000 130000 130000 130000 130000 130000 130000 130000 130000 130000										130000 130000 130000 130000 130000 130000 130000 130000 130000 130000									
130000 130000 130000 130000 130000 130000 130000 130000 130000 130000										130000 130000 130000 130000 130000 130000 130000 130000 130000 130000									

BC

PROCESSES AND PROPERTIES UNDER
STANDARD CONDITIONS

Determination of dipole moments of fatty acids in solution by Debye's second method. M. P. Voliarovitch and N. N. Stepanenko (*Izv. Akad. Nauk SSSR, Ser. Khim.*, 1960, No. 647-658).—Vals. of μ , determined at $\lambda = 2.5 \text{ m}$, are recorded for stearic, oleic, and lauric acids and triolein in solutions of varied concn. The vals. agree with those obtained by other methods.
P. L. U.

A-1

ASACSLA METALLURGICAL LITERATURE CLASSIFICATION

PRINCIPAL AND PROPERTY INDEX

Determination of dipole moments in molecules of the aliphatic acids C_4 in benzene, cyclohexane and methylcyclohexane solutions. N. Stepanenko, J. Expt. Theoret. Phys. (U.S.S.R.) 16, 163-70(1944).—The dielect. coeffs. were measured by means of a Debye-Contingue app. as modified by Potapenko, with a 2.5-m. wave. The polarizations P_0 at 18° were found to be: oleic acid in benzene 123.6 cc.; in cyclohexane 129.0 cc.; in methylcyclohexane 127.0 cc.; for lauric acid 148.0 cc., 129.3 cc., 131.5 cc. The values of μ are, resp., 1.22, 1.13, 1.09 and 1.26, 1.26, 1.204. For oleic acid at 40°, $P_0 = 126.3$ and $\mu = 1.16$. Cryoscopic data on oleic acid indicate considerable anisot. in benzene and cyclohexane solns. at concns. above 0.001 molar. In dioxane soln. no anisot. sets in up to 0.03 molar, whereas below 0.005 molar there is even considerable diisot. The detailed exptl. data are shown.

F. H. Rathmann

Physics Lab., Zagorskiy State Teachers Inst.

CA

2

Dipole moments of stearic acid and tristearin as determined in their cyclohexane, benzene and dioxane solutions. N. Stepanenko and V. Agronov. *J. Exptl. Theoret. Phys. (U.S.S.R.)* 19, 258-31 (1944).—With a wave length of 301.5 m. the dielec. coeff. of solns. of stearic acid and tristearin in dioxane, cyclohexane and benzene were detd. The dipole moments were found by detg. the polarizations. The dipole moment of stearic acid in dioxane is greater than that in cyclohexane and less than that of oleic and linoleic acids in the same solvents. The polarization P_0 and dipole moments $\mu \times 10^{18}$ of stearic acid in dioxane are 160 cc., 1.00; in cyclohexane 128.3 cc., 1.04; of oleic acid 108.0 cc., 1.08; 130.0 cc., 1.13; and of linoleic acid 102.5 cc., 1.71; 130.3 cc., 1.85, resp.; of tristearin in dioxane 484 cc., 2.68; in benzene 472 cc., 2.83; and of tristearin 548 cc., 3.05 and 547 cc., 3.08, resp. The data obtained are discussed from the standpoints of mol. structure and conformation. The degree of association in dioxane soln. as calcd. according to Wolf from $\mu = (P_0 - P_1)/P_0$ are stearic acid 0.42, oleic acid 0.30, linoleic acid 0.20, tristearin 0.20 and tristearin 0.06.

P. H. Rathmann

ASAC-55A METALLURGICAL LITERATURE CLASSIFICATION

11000 110001100

110000 110000 110000

110000 110000

110000 110000

110000 110000 110000

110000 110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

110000

2

Determination of the dipole moments of unsaturated fat acids in dioxane solution. M. Volarovich and N. Semanenko. *J. Exptl. Theoret. Phys. (U.S.S.R.)* 14, 813-17 (1944).—With a Debye-Coulidge app. and a wave length of 3.5 m, the dielec. consts. of solns. of unsatd. fat acids in dioxane soln. were detd. for various concns. from 0 to 1.0 molar. The polarizations and the dipole moments were found to be, resp.: linoleic acid $P_{\infty} = 162.5$ cc., $\mu = 1.71$; oleic acid 168 cc., 1.80; and tridecic 545 cc., 3.00. The values for these acids are higher than those found for the same acids under like conditions in benzene or toluene soln. This difference is considered indicative of partial assocn. in dioxane soln.; the degree of assocn. is about $1/6$.
F. H. Rathmann

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44																									
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z AA AB AC AD AE AF AG AH AI AJ AK AL AM AN AO AP AQ AR AS AT AU AV AW AX AY AZ BA BB BC BD BE BF BG BH BI BJ BK BL BM BN BO BP BQ BR BS BT BU BV BW BX BY BZ CA CB CC CD CE CF CG CH CI CJ CK CL CM CN CO CP CQ CR CS CT CU CV CW CX CY CZ DA DB DC DE DF DG DH DI DJ DK DL DM DN DO DP DQ DR DS DT DU DV DW DX DY DZ EA EB EC ED EE EF EG EH EI EJ EK EL EM EN EO EP EQ ER ES ET EU EV EW EX EY EZ FA FB FC FD FE FF FG FH FI FJ FK FL FM FN FO FP FQ FR FS FT FU FV FW FX FY FZ GA GB GC GD GE GF GG GH GI GJ GK GL GM GN GO GP GQ GR GS GT GU GV GW GX GY GZ HA HB HC HD HE HF HG HH HI HJ HK HL HM HN HO HP HQ HR HS HT HU HV HW HX HY HZ IA IB IC ID IE IF IG IH II IJ IK IL IM IN IO IP IQ IR IS IT IU IV IW IX IY IZ JA JB JC JD JE JF JG JH JI JJ JK JL JM JN JO JP JQ JR JS JT JU JV JW JX JY JZ KA KB KC KD KE KF KG KH KI KJ KL KM KN KO KP KQ KR KS KT KU KV KW KX KY KZ LA LB LC LD LE LF LG LH LI LJ LK LL LM LN LO LP LQ LR LS LT LU LV LW LX LY LZ MA MB MC MD ME MF MG MH MI MJ MK ML MN MO MP MQ MR MS MT MU MV MW MX MY MZ NA NB NC ND NE NF NG NH NI NJ NK NL NO NP NQ NR NS NT NU NV NW NX NY NZ OA OB OC OD OE OF OG OH OI OJ OK OL OM ON OO OP OQ OR OS OT OU OV OW OX OY OZ PA PB PC PD PE PF PG PH PI PJ PK PL PM PN PO PP PQ PR PS PT PU PV PW PX PY PZ QA QB QC QD QE QF QG QH QI QJ QK QL QM QN QO QP QQ QR QS QT QU QV QW QX QY QZ RA RB RC RD RE RF RG RH RI RJ RK RL RM RN RO RP RQ RR RS RT RU RV RW RX RY RZ SA SB SC SD SE SF SG SH SI SJ SK SL SM SN SO SP SQ SR SS ST SU SV SW SX SY SZ TA TB TC TD TE TF TG TH TI TJ TK TL TM TN TO TP TQ TR TS TT TU TV TW TX TY TZ UA UB UC UD UE UF UG UH UI UJ UK UL UM UN UO UP UQ UR US UT UU UV UW UX UY UZ VA VB VC VD VE VF VG VH VI VJ VK VL VM VN VO VP VQ VR VS VT VU VV VW VX VY VZ WA WB WC WD WE WF WG WH WI WJ WK WL WM WN WO WP WQ WR WS WT WU WV WW WX WY WZ XA XB XC XD XE XF XG XH XI XJ XK XL XM XN XO XP XQ XR XS XT XU XV XW XX XY XZ YA YB YC YD YE YF YG YH YI YJ YK YL YM YN YO YP YQ YR YS YT YU YV YW YX YY YZ ZA ZB ZC ZD ZE ZF ZG ZH ZI ZJ ZK ZL ZM ZN ZO ZP ZQ ZR ZS ZT ZU ZV ZW ZX ZY ZZ																									
<p>CA</p> <p>27</p> <p>DETERMINATION OF MOISTURE IN OIL, MAZUT, AND SIMILAR LIQUIDS. V. A. Golubtsov, N. N. Stepanenko, and N. V. Vargavtik. U.S.S.R. 64,822, May 31, 1915. Moisture is detd. by comparing the dielectric properties of the sample with those of a water-free sample of the same liquid.</p> <p>M. Hosh</p>																									
<p>ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION</p>																									

CA

1ST AND 2ND ORDERS

PROCESSES AND PROPERTIES INDEX

1ST AND 4TH ORDERS

2

The dielectric constants and absorption coefficients of fatty acids and triglycerides. N. Stepanenko and T. Novikova (Zagorsk State Pedagogic Inst.). *Atta Physicochim. U.R.S.S.* 20, 683-68 (1948).—The dielec. constn. and absorption coeffs. were detd. at a wave length of 3.44 m. at temps. from -60° to 100° for stearic, oleic, and linoleic acids and for tristearin and triolein. Various proposed formulas were tried for relating the results to the dipole moments of the same compds. measured in soln., but all failed, presumably because of mol. assocn.

A. O. Allen

Common Elements

Common Variable Index

OPEN

MATERIALS INDEX

Zagorsk State Pedagogic Inst., Physics Lab.

ASB-SLA METALLURGICAL LITERATURE CLASSIFICATION

147080 24

147080 41P QM QM

CELLULOSE

147080 41P QM QM

147080 41P QM QM

CA

Dipole moments of stearic and palmitic acids and their triglycerides. N. Sijpekenhu, V. Agranat, and T. Novikova. *Acta Physicochim.* 27: 35, 682-91 (1945); cf. C. A. 39, 1324^u.—Dipole moments in Debye, calcd. from dil. soln. measurements at 22-3°, were obtained in diisone (D), cyclohexane (C), and benzene (B) as follows: palmitic acid D 1.76, C 0.81, B 0.76; stearic acid D 1.68, C 1.04; tripalmitin D 2.90, B 2.77; tristearin D 2.98, B 2.81. On the assumption that (1) only acid monomers are present in diisone and (2) any dimers in other solvents have zero moment, the degree of assocn. of the acids was calcd. and indicated that 80-85% of palmitic and stearic acid moles are assocd. in pairs in a cyclohexane soln. (2 vol. %). Tripalmitin and tristearin show no noticeable assocn.

Oscar T. Quimby

Oscar T. Quimby

A 30-11 A METALLURGICAL LITERATURE CLASSIFICATION

STEPANENKO, N. N.

"Dipole Moments of the Palmitic Acid and Tripalmitin Determined in Benzene, Cyclohexane, and Dioxane Solutions," Zhur. eksper. i teoret. fiz., 16, No.6, 1946

Physics Lab., Zagorsk State Pedagogic Inst.

STEPANENKO, N. N.

PA 18T76

USSR/Chemistry - Fatty Acids
Chemistry - Glycerides

Jun 1946

"The Dielectric Constants and Absorption Coefficients
of Fatty Acids and Triglycerides," N. N. Stepanenko,
T. P. Novikova, A. P. Kerman, 8 pp

"Zhur Fiz Khim" Vol XX, No 6

Account of experiments conducted according to the
Drude-Coolidge method with wave length of 3.44 meters
and temperatures of 2 to 3 degrees. Results in graph
and tabular form are given for stearic acid, oleic
acid, linoleic acid and tristearin.

Zagorsk State Teachers College, Moscow

18T76

STEPANENKO, N.N.

VARGAFTIK, N.B.; GOLUBTSOV, V.A.; STEPANENKO, N.N.

[Electrical method of determining moisture content in petroleum products] Elektricheskii metod opredeleniia vlazhnosti nefteproduktov. Moskva, Gos. izd-vo tekhniko-teoret. lit-ry, 1947.
58 p.
(MLRA 7:2)
(Petroleum products)

STEPANENKO, N. N.

IC

34711

USSR/Chemistry - Electrolytes
Chemistry - Emulsions

Feb 1947

"The Influence of the Concentration of Electrolytes in Water Present in Oil, on the Dielectric Constant of the Latter," N. N. Stepanenko, N. B. Vargafik, M. S. Araf'yev, Physics Laboratory, Institute of Construction, Moscow, 2 pp

"Kolloidny Zhurnal" Vol IX, No 2

Several scientists, among them Frenkel, have advanced the theory that it might be possible to apply Coulomb's electrical method for determining the moisture content of petroleum products. As a result, the authors describe the experiments which they conducted

USSR/Chemistry - Electrolytes (Contd) Feb 1947

to determine the effect of the concentration of electrolytes in water which is found in oil, and the effect this has on the dielectric constant of the oil. In the experiments the dielectric constant determined the capacity of the condenser.

CH

2

PROCESSED AND PROPERTY INDEX

Dielectric polarization and dipole moments of stearic and oleic acids determined in cyclohexane solutions at different temperatures. N. M. Gerasimova, N. A. Agumai, and V. P. Yakovlev (Institute of Chemistry, Acad. Sci. USSR, Moscow). *J. Phys. Chem. (U.S.S.R.)* 21, 553-7 (1947) (in Russian). -- The dielectric constant of cyclohexane solutions of stearic and oleic acids. The dipole moments (times 10^{-18} e.s.u.) at 25, 50, 70, and 75° are for stearic acid 0.87, 0.78, 0.68, and 1.00, and for oleic acid 1.12, 1.24, 1.51, and 1.60, resp. The variation of the dipole moment with temp. and its low magnitude are attributed to assocn. of acid mole. The degree of assocn. is calcd. J. J. Esherman

COMMON ELEMENTS

COMMON VARIABLE ELEMENTS

OPEN

MATERIALS INDEX

ASS-514 METALLURGICAL LITERATURE CLASSIFICATION

FROM STAINLESS

100000 417 000 000

RELIABLE

0011271 000 000 101

100000 417 000 000

0011271 000 000 101

100000 417 000 000

0011271 000 000 101

STEPANENKO, N. N.

Chemical Abst.

Vol. 48 No. 8

Apr. 25, 1954

Fuels and Carbonization Products

Electric properties of peat. N. N. Stepanenko, I. E. Belokopytov, and N. A. Hlogomolov, *Chem. Z. (U.S.S.R.)*, 14, 597-9(1952)(Engl. translation).--See C.A. 47, 3513b. 4- H. L-II.

STEPANENKO, N.N.; BOGDANOV, L.I.

Dielectric polarization and dipole moment of linolenic acid in benzene
and in dioxane. Zhur. Fiz.Khim. 26, 1472-6 '52. (MLRA 5:12)
(CA 47 no.13:6201 '53)

STEPANENKO, N.N.

BOGDANOV, L.I.; STEPANENKO, N.N.

Dielectric constant and absorption coefficients of tripalmitin.
Zhur. Fiz. Khim. 26, 1477-9 '52. (MLBA 5:12)
(CA 47 no.13:6201 '53)

242T14

USSR/Chemistry - Dioxane

Nov 52

"The Dielectric Permeability and the Coefficients of Absorption of Dioxane," N. A. Bogomolov and N. N. Stepanenko, Second State Med Inst, Moscow

"Zhur Fiz Khim" Vol 26, No 11, pp 1664-665

With an arrangement based on the Drude-Coolidge method, and using waves of 1.5 m and 63.5 cm, the authors measured the dielectric permeability and coeffs of absorption of dioxane and computed the values of its polarization at different temps. The

242T14

data obtained led to the conclusion that dioxane is non-polar. The coeffs of absorption for dioxane appeared equal to zero in the range of temps investigated.

STEINBERG, L. F.

242T14

STEPANENKO, N. N.

Chemical Abst.
Vol. 48 No. 6
Mar. 25, 1954
General and Physical Chemistry

3

Dielectric constant and absorption coefficients of linolenic acid. L. I. Chibrikov and N. N. Stepanenko (Zaporozh. Pedagog. Inst.). Zhur. Fiz. Khim. 27, 1481-4 (1953); cf. C.A. 47, 6201f. — The dielec. consts. ϵ of linolenic acid are 2.55, 2.76, 2.97, and 3.01 at -10° , 20° , 60° , and 100° , resp. The absorption coeff. is 0.03, 0.07, and 0.08 at -10° , $40-60^\circ$, and $80-100^\circ$, resp. For stearic, oleic, linoleic, and linolenic acids, ϵ is a linear function of the iodine no. The Drude-Coolidge method, with 64-cm. waves, was used for the measurements. J. J. Bikerman

11-5-54

STEPANENKO, N.N., professor (Moskva); SOKOLOV, N.A., dotsent (Moskva)

Fiftieth anniversary of the death of Pierre Curie. Fel'd. i akush.
21 no.6:29-32 Je '56. (MLBA 9:9)
(CURIE, PIERRE, 1859-1906)

Stepanenko, N.N.

USSR/Physical Chemistry - Thermodynamics, Thermochemistry, Equilibria,
Physical-Chemical Analysis, Phase Transitions.

B-8

Abs Jour: Referat. Zhurnal Khimiya, No 2, 1958, 3766.

Author : M.M. Popov, Yu.V. Gagarinskiy, N.N. Stepanenko.

Inst :

Title : Dissociation Pressure of $\text{Li}_2\text{SO}_4 \cdot \text{H}_2\text{O}$ at 25 to 45°.

Orig Pub: Zh. neorgan. khimii, 1957, 2, No 7, 1457-1459.

Abstract: The dissociation pressure of $\text{Li}_2\text{SO}_4 \cdot \text{H}_2\text{O}$ was measured at 25 to 45° with differential tensimeters. The adjusted mean experimental values satisfy the equation $\log P$ (mm of merc. col.) = $10.228 - 2967/T$. The calculated heat of Li_2SO_4 hydration by liquid water is 3.18 kcal per mole.

Card : 1/1

-15-

BORDIKOVA, A.I., dots., kand.biol.nauk; STEPANENKO, N.N., prof., doktor fiz.-
mat.nauk

Remizov frigorimeter and its use in solving certain problems.
Nauch.dokl.vys.shkoly; stroi. no.3:274-279 '58. (MIRA 12:7)

1. Rekomendovana kafedroy fiziki Moskovskogo instituta inzhenerov
gorodskogo stroitel'stva Mosgorispolkoma.
(Thermometers and thermometry)

STEPANENKO, N.P.

Minutes of the Fifth Meeting of the Kiev Province Scientific
Society of Doctors and Otolaryngologists on September 10, 1958.
Zhur. ush., nos. i gorl. bol. 19 no.5:93-94 S.O '59. (MIRA 14:10)
(ODESSA PROVINCE--OTOLARYNGOLOGICAL SOCIETIES)

STEPANENKO, N.P.

Minutes of the Sixth Meeting of the Kiev Province Scientific
Society of Doctors and Otolaryngologists on October 31, 1958.
Zhur. ush., nos. i gorl. bol. 19 no.5:94-96 S-0 '59. (MIRA 14:10)
(ODESSA PROVINCE--OTOLARYNGOLOGICAL SOCIETIES)

STEPANENKO, O.R., st. nauchn. sotr., otv. red.; LITVAK, L.B., zasl. deyatel' nauki, prof., zam. otv. red.; MAN'KOVSKIY, B.N., prof., red.; PANCHENKO, D.I., zasl. deyatel' nauki, prof., red.; TATARENKO, N.P., zasl. deyatel' nauki, prof., red.; SOKOLYANSKIY, G.G., prof., red.; GOLUBOVA, R.A., st. nauchn. sotr., red.

[Disorders of cerebral blood circulation (in the neurological clinic)] Rasstroistva mozgovogo krovoobrashchenia (v nevrologicheskoi klinike). Kiev, Zdorov'ia, 1965. 258 p.
(MIRA 18:9)

1. Ukrainskiy nauchno-issledovatel'skiy psikhonevrologicheskii institut. 2. Ukrainskiy nauchno-issledovatel'skiy psikhonevrologicheskii institut (for Litvak). 3. Otdel nevrologii Ukrainского nauchno-issledovatel'skogo psikhonevrologicheskogo instituta (for Golubova). 4. Otdel vegetativnoy patologii Ukrainского nauchno-issledovatel'skogo psikhonevrologicheskogo instituta (for Stepanenko). 5. Kafedra nervnykh bolezney Donetskogo meditsinskogo instituta (for Panchenko).